Bolon Fact Sheet

Artisan Collection

BOLON

Bolon

Bolon is a textured woven flooring, consisting a profile section PVC warp (vertical weave), with a PVC encased polyester weft (horizontal weave) fixed to a plasticised PVC backing with an interlayer of fibreglass. The Artisan collection includes 12 articles and is available in roll, tile and plank form.

Arisan Collection



Design

The Artisan Collection combines the craftsmanship and creativity of yesteryear with the possibilities achievable by modern technology. The result is a collection with a new thread, high textile feeling, high wear resistance class and a unique look.

Fast Facts

• Roll size = 25 m x 2 m at 2.5 mm thick.

Weight of rolls = 2.9 kg/m^2 .

• Tile Standard tile size = 500 x 500 mm at 3 mm thick.

Weight of tiles = 3.9 kg/m^2 .

Tiles sold by the box = 20 tiles/5 m^2 .

• Plank Standard plank size = 667 x 222 mm at 3 mm thick.

Weight of planks 3.9 kg/m².

Sold by the box in either portrait or landscape weave 27 planks/4 m².

• Studio Available in Bolon Studio shapes.

Visit <u>bolon.theandrewsgroup.com.au</u> or contact The Andrews Group for details.

Technical Specifications

Article Name		Roll	Tile	Plank	Wear Class	Wear Rating	Warranty Years	W.O.R. Slip	Pend Test Wet Slip	Sound Reduction	Sound Absorption	Fire Rating NCC C1.10a
Artisan	Coal	✓	✓	✓	33	EHD	15	R10	P2	11dB	5%	Pass
	Slate	✓	✓	✓	33	EHD	15	R10	P2	11dB	5%	Pass
	Concrete	✓	1	✓	33	EHD	15	R10	P2	11dB	5%	Pass
	lvory	√	Х	Х	33	EHD	15	R10	P2	11dB	5%	Pass
	Petroleum	√	1	Х	33	EHD	15	R10	P2	11dB	5%	Pass
	Denim	√	✓	Х	33	EHD	15	R10	P2	11dB	5%	Pass
	Jade	✓	✓	Χ	33	EHD	15	R10	P2	11dB	5%	Pass
	Malachite	✓	1	Х	33	EHD	15	R10	P2	11dB	5%	Pass
	Sienna	✓	✓	Х	33	EHD	15	R10	P2	11dB	5%	Pass
	Fuchsia	✓	1	Х	33	EHD	15	R10	P2	11dB	5%	Pass
	Quartz	✓	✓	Х	33	EHD	15	R10	P2	11dB	5%	Pass
	Ecru	√	1	Х	33	EHD	15	R10	P2	11dB	5%	Pass

- Wear Rating
 Classified 33 under international standard EN685 rating, the Artisan Collection can be used in all areas of commercial and residential applications. Please contact The Andrews Group for specific recommendations on area and colour selection.
- Warranty The Artisan Collection is warranted for 15 years in areas defined as fit for purpose.
 The terms and conditions of this warranty are available on request.
- Fire Rating

 The Artisan Collection has a Critical Radiant Flux (CRF) rating of 6.7 kW/m², and a smoke developed rating of 205 %mins, as tested to ISO9239.1. This allows the product to be installed in any areas of a commercial building under the requirements of the National Construction Code (NCC).

Technical Specifications

 Slip Rating The Artisan Collection is rated R10 under the Wet Oil Ramp test as defined in S4586. The Artisan Collection is rated P2 under the Wet Pendulum Test as defined in AS4586 (2013). These ratings indicate a reduced risk of slip with this product.

• Sound Rating The Artisan Collection reduces impact sound by 11 decibels when adhered directly to a concrete slab. The Artisan Collection reduces airborne sound by 5% when adhered to a concrete slab. These measurements are defined by ISO717.1/2, and mean that the product contributes positively to sound insulation in commercial and

residential buildings.

Installation
 Please refer to Bolon Installation Guidelines or contact the Customer Service Team

at The Andrews Group

+61 (03) 9827 1311 | bolon@theandrewsgroup.com.au

Service Team at The Andrews Group

+61 (03) 9827 1311 | bolon@theandrewsgroup.com.au