Bolon Fact Sheet

BKB Collection

BOLON

Bolon

Bolon is a textured woven flooring, consisting a profile section PVC warp (vertical weave), with a PVC encased polyester weft (horizontal weave) fixed to a plasticised PVC backing with an interlayer of fibreglass. The BKB collection includes 8 articles and is available in roll and tile form.

BKB Collection



Design

The BKB Collection is inspired sisal and coir mats for its discreet versatility. As Bolon's first collection, the broad colour palette is classic and has a wide range of applications.

Fast Facts

• Roll size = 25 m x 2 m at 2.5 mm thick.

Weight of rolls = 2.9 kg/m^2 .

• Tile Standard tile size = 500 x 500 mm at 3 mm thick.

Weight of tiles = 3.9 kg/m².

Tiles sold by the box = 20 tiles/5 m^2 .

• Studio Available in Bolon Studio shapes.

Visit bolon.theandrewsgroup.com.au or contact The Andrews Group for details.

Technical Specifications

Article Name		Roll	Tile	Wear Class		Wear	Warranty	W.O.R.	Pend Test	Sound	Sound	Fire Rating
				Roll	Tile	Rating	Years	Slip	Wet Slip	Reduction	Absorption	NCC C1.10a
ВКВ	Sisal Plain Granite	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass
	Sisal Plain Mole	✓	1	32	32	HD	10	R10	P3	12dB	5%	Pass
	Sisal Plain Black	✓	√	32	32	HD	10	R10	P3	12dB	5%	Pass
	Sisal Plain Sand	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass
	Sisal Plain Steel	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass
	Sisal Natur Black	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass
	Metallic Alpha	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass
	Sisal Plain Beige	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass

Wear Rating

Classified 32 under international standard EN685 rating, the BKB Collection can be used in all areas of commercial and residential applications. Please contact The Andrews Group for specific recommendations on area and colour selection.

Warranty

The BKB Collection is warranted for 10 years in areas defined as fit for purpose. The terms and conditions of this warranty are available on request.

· Fire Rating

The BKB Collection has a Critical Radiant Flux (CRF) rating of 8.4 kW/m², and a smoke developed rating of 189 %mins, as tested to ISO9239.1. This allows the product to be installed in any areas of a commercial building under the requirements of the National Construction Code (NCC).

Technical Specifications

Slip Rating
 The BKB Collection is rated R10 under the Wet Oil Ramp test as defined in AS4586.
 The BKB Collection is rated P3 under the Wet Pendulum Test as defined in AS4586.
 These ratings indicate a reduced risk of slip with this product.

Sound Rating The BKB Collection reduces impact sound by 12 decibels when adhered directly to
a concrete slab. The BKB Collection reduces airborne sound by 5% when adhered
to a concrete slab.

Installation
 Please refer to Bolon Installation Guidelines or contact the Customer Service Team
 at The Andrews Group
 +61 (03) 9827 1311 | bolon@theandrewsgroup.com.au

Maintenance Please refer to Bolon Maintenance Guidelines or contact the Customer
 Service Team at The Andrews Group

+61 (03) 9827 1311 | bolon@theandrewsgroup.com.au