

Bolon Fact Sheet

Botanic Collection

BOLON

Botanic Collection

Bolon

Bolon is a textured woven flooring, consisting a profile section PVC warp (vertical weave), with a PVC encased polyester weft (horizontal weave) fixed to a plasticised PVC backing with an interlayer of fibreglass. The Botanic collection includes 10 articles and is available in roll and tile form.

Botanic Collection



Viola



Viva



Thyme



Cilia



Kale



Tulip



Sage



Osier



Garden



Tilia

Botanic Collection

Design

The Botanic Collection is inspired by the wealth of detail in nature. With a two-coloured weft thread, the richly coloured collection provides a varied range of muted earth tones and bright accents.

Fast Facts

- Roll Roll size = 25 m x 2 m at 2.5 mm thick.
Weight of rolls = 2.9 kg/m².
- Tile Standard tile size = 500 x 500 mm at 3 mm thick.
Weight of tiles = 3.9 kg/m².
Tiles sold by the box = 20 tiles/5 m².
- Studio Available in Bolon Studio shapes.
Visit bolon.theandrewsgroup.com.au or contact The Andrews Group for details.

Botanic Collection

Technical Specifications

Article Name	Roll	Tile	Wear Class		Wear Rating	Warranty Years	W.O.R. Slip	Pend Test Wet Slip	Sound Reduction	Sound Absorption	Fire Rating NCC C1.10a	
			Roll	Tile								
Botanic	Viola	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass
	Thyme	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass
	Sage	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass
	Viva	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass
	Kale	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass
	Tulip	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass
	Tilia	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass
	Garden	✓	X	32	-	HD	10	R10	P3	12dB	5%	Pass
	Cilia	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass
	Osier	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass

- Wear Rating** Classified 32 under international standard EN685 rating, the Botanic Collection can be used in all areas of commercial and residential applications. Please contact The Andrews Group for specific recommendations on area and colour selection.
- Warranty** The Botanic Collection is warranted for 10 years in areas defined as fit for purpose. The terms and conditions of this warranty are available on request.
- Fire Rating** The Botanic Collection has a Critical Radiant Flux (CRF) rating of 7.4 kW/m², and a smoke developed rating of 189 %mins, as tested to ISO9239.1. This allows the product to be installed in any areas of a commercial building under the requirements of the National Construction Code (NCC).

Botanic Collection

Technical Specifications

- Slip Rating The Botanic Collection is rated R10 under the Wet Oil Ramp test as defined in AS4586. The Botanic Collection is rated P3 under the Wet Pendulum Test as defined in AS4586 (2013). These ratings indicate a reduced risk of slip with this product.
- Sound Rating The Botanic Collection reduces impact sound by 12 decibels when adhered directly to a concrete slab. The Botanic Collection reduces airborne sound by 5% when adhered to a concrete slab.
- Installation Please refer to Bolon Installation Guidelines or contact the Customer Service Team at The Andrews Group
+61 (03) 9827 1311 | bolon@theandrewsgroup.com.au
- Maintenance Please refer to Bolon Maintenance Guidelines or contact the Customer Service Team at The Andrews Group
+61 (03) 9827 1311 | bolon@theandrewsgroup.com.au