

Bolon Fact Sheet

Create Collection

BOLON

Create Collection

Bolon

Bolon is a textured woven flooring, consisting a profile section PVC warp (vertical weave), with a PVC encased polyester weft (horizontal weave) fixed to a plasticised PVC backing with an interlayer of fibreglass. The Create collection includes 5 articles and is available in roll and tile form.

Create Collection



Inducto




Comar



Facio



Converso



Fabrico

Create Collection

Design

The Create Collection is the world's first designer flooring that uses a novel method of weaving that produces a profiled yarn – a thread with a textured surface that can be used for jacquard weave. This gives the floor both three-dimensional and light reflecting effects that bring any interior environment to life.

Fast Facts

- Roll Roll size = 25 m x 2 m at 2.5 mm thick.
 Weight of rolls = 2.9 kg/m².
- Tile Standard tile size = 500 x 500 mm at 3 mm thick.
 Weight of tiles = 3.9 kg/m².
 Tiles sold by the box = 20 tiles/5 m².
- Studio Available in Bolon Studio shapes.
 Visit bolon.theandrewsgroup.com.au or contact The Andrews Group for details.

Create Collection

Technical Specifications

Article Name	Roll	Tile	Wear Class		Wear Rating	Warranty Years	W.O.R. Slip	Pend Test Wet Slip	Sound Reduction	Sound Absorption	Fire Rating NCC C1.10a	
			Roll	Tile								
Create	Inducto	✓	✓	33	33	EHD	15	R10	P2	11dB	5%	Pass
	Comar	✓	✓	33	33	EHD	15	R10	P2	11dB	5%	Pass
	Facio	✓	✓	33	33	EHD	15	R10	P2	11dB	5%	Pass
	Converso	✓	✓	33	33	EHD	15	R10	P2	11dB	5%	Pass
	Fabrico	✓	✓	33	33	EHD	15	R10	P2	11dB	5%	Pass

- Wear Rating** Classified 33 under international standard EN685 rating, the Create Collection can be used in all areas of commercial and residential applications. Please contact The Andrews Group for specific recommendations on area and colour selection.
- Warranty** The Create Collection is warranted for 15 years in areas defined as fit for purpose. The terms and conditions of this warranty are available on request.
- Fire Rating** The Create Collection has a Critical Radiant Flux (CRF) rating of 6.7 kW/m², and a smoke developed rating of 205 %mins, as tested to ISO9239.1. This allows the product to be installed in any areas of a commercial building under the requirements of the National Construction Code (NCC).

Create Collection

Technical Specifications

- Slip Rating The Create Collection is rated R10 under the Wet Oil Ramp test as defined in AS4586. The Create Collection is rated P2 under the Wet Pendulum Test as defined in AS4586 (2013). These ratings indicate a reduced risk of slip with this product.
- Sound Rating The Create Collection reduces impact sound by 11 decibels when adhered directly to a concrete slab. The Create Collection reduces airborne sound by 5% when adhered to a concrete slab. These measurements are defined by ISO717.1/2, and mean that the product contributes positively to sound insulation in commercial and residential buildings.
- Installation Please refer to Bolon Installation Guidelines or contact the Customer Service Team at The Andrews Group
+61 (03) 9827 1311 | bolon@theandrewsgroup.com.au
- Maintenance Please refer to Bolon Maintenance Guidelines or contact the Customer Service Team at The Andrews Group
+61 (03) 9827 1311 | bolon@theandrewsgroup.com.au