Bolon Fact Sheet

Elements Collection

BOLON

Bolon

Ash

Cork

Bolon is a textured woven flooring, consisting a profile section PVC warp (vertical weave), with a PVC encased polyester weft (horizontal weave) fixed to a plasticised PVC backing with an interlayer of fibreglass. The Elements collection includes 10 articles and is available in roll, tile and with ISI comfort backing.

Elements Collection



Design

Creating balance between people, objects and their surroundings, Elements is a discreet collection, characterised by warm tones, a natural balance and sustainable values.

Fast Facts

• Roll size = 25 m x 2 m at 2.5 mm thick.

Weight of rolls = 2.9 kg/m^2 .

• Tile Standard tile size = 500 x 500 mm at 3 mm thick.

Weight of tiles = 3.9 kg/m².

Tiles sold by the box = 20 tiles/5 m^2 .

Also available with ISI comfort backing.

Standard tile size = 500 x 500 mm at 5 mm thick.

Weight of tiles= 4.1 kg/m²

Tiles sold by the box = 12 tiles/3 m^2

• Studio Available in Bolon Studio shapes.

Visit bolon.theandrewsgroup.com.au or contact The Andrews Group for details.

Technical Specifications

Article Name		Roll	Tile	Wear Class		Wear	Warranty	W.O.R.	Pend Test	Sound	Sound	Fire Rating
				Roll	Tile	Rating	Years	Slip	Wet Slip	Reduction	Absorption	NCC C1.10a
Elements	Wool	✓	✓	33	33	EHD	15	R10	P2	11dB	5%	Pass
	Flint	✓	✓	33	33	EHD	15	R10	P2	11dB	5%	Pass
	Marble	✓	✓	33	33	EHD	15	R10	P2	11dB	5%	Pass
	Walnut	✓	✓	33	33	EHD	15	R10	P2	11dB	5%	Pass
	Silk	✓	✓	33	33	EHD	15	R10	P2	11dB	5%	Pass
	Birch	✓	✓	33	33	EHD	15	R10	P2	11dB	5%	Pass
	Linen	✓	✓	33	33	EHD	15	R10	P2	11dB	5%	Pass
	Oak	✓	✓	33	33	EHD	15	R10	P2	11dB	5%	Pass
	Ash	✓	✓	33	33	EHD	15	R10	P2	11dB	5%	Pass
	Cork	✓	✓	33	33	EHD	15	R10	P2	11dB	5%	Pass

- Wear Rating Classified 33 under international standard EN685 rating, the Elements Collection
 can be used in all areas of commercial and residential applications. Please contact
 The Andrews Group for specific recommendations on area and colour selection.
- Warranty The Elements Collection is warranted for 15 years in areas defined as fit for purpose. The terms and conditions of this warranty are available on request.
- Fire Rating
 The Elements Collection has a Critical Radiant Flux (CRF) rating of 6.7 kW/m², and a smoke developed rating of 205 %mins, as tested to ISO9239.1. This allows the product to be installed in any areas of a commercial building under the requirements of the National Construction Code (NCC).

Technical Specifications

Slip Rating
 The Elements Collection is rated R10 under the Wet Oil Ramp test as defined in

AS4586. The Elements Collection is rated P2 under the Wet Pendulum Test as defined in AS4586 (2013). These ratings indicate a reduced risk of slip with

this product.

• Sound Rating The Elements Collection reduces impact sound by 11 decibels when adhered

directly to a concrete slab. The Elements Collection reduces airborne sound by 5% when adhered to a concrete slab. These measurements are defined by ISO717.1/2, and mean that the product contributes positively to sound insulation in commercial

and residential buildings.

Installation
 Please refer to Bolon Installation Guidelines or contact the Customer Service Team

at The Andrews Group

+61 (03) 9827 1311 | bolon@theandrewsgroup.com.au

Maintenance
 Please refer to Bolon Maintenance Guidelines or contact the Customer

Service Team at The Andrews Group

+61 (03) 9827 1311 | bolon@theandrewsgroup.com.au