

Bolon Fact Sheet

Now Collection

BOLON

Now Collection


Bolon

Bolon is a textured woven flooring, consisting a profile section PVC warp (vertical weave), with a PVC encased polyester weft (horizontal weave) fixed to a plasticised PVC backing with an interlayer of fibreglass. The Now collection includes 6 articles and is available in roll and tile form.

Now Collection



Anthracite




Silver




Champagne



Titanium



Copper



Brass

Now Collection

Design

The Now Collection exudes luxury and opulence with its metallic sheen, making it our most luminous flooring range. This dramatic collection creates visually powerful environments with a strong sense of design unity.

Fast Facts

- Roll Roll size = 25 m x 2 m at 2.5 mm thick.
Weight of rolls = 2.9 kg/m².
- Tile Standard tile size = 500 x 500 mm at 3 mm thick.
Weight of tiles = 3.9 kg/m².
Tiles sold by the box = 20 tiles/5 m².
- Studio Available in Bolon Studio shapes.
Visit bolon.theandrewsgroup.com.au or contact The Andrews Group for details.

Now Collection

Technical Specifications

Article Name	Roll	Tile	Wear Class		Wear Rating	Warranty Years	W.O.R. Slip	Pend Test Wet Slip	Sound Reduction	Sound Absorption	Fire Rating NCC C1.10a
			Roll	Tile							
Now Anthracite	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass
Titanium	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass
Silver	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass
Brass	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass
Copper	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass
Champagne	✓	✓	32	32	HD	10	R10	P3	12dB	5%	Pass

- Wear Rating** Classified 32 under international standard EN685 rating, the Now Collection can be used in all areas of commercial and residential applications. Please contact The Andrews Group for specific recommendations on area and colour selection.
- Warranty** The Now Collection is warranted for 10 years in areas defined as fit for purpose. The terms and conditions of this warranty are available on request.
- Fire Rating** The Now Collection has a Critical Radiant Flux (CRF) rating of 7.4 kW/m², and a smoke developed rating of 189 %mins, as tested to ISO9239.1. This allows the product to be installed in any areas of a commercial building under the requirements of the National Construction Code (NCC).

Now Collection

Technical Specifications

- Slip Rating The Now Collection is rated R10 under the Wet Oil Ramp test as defined in AS4586. The Now Collection is rated P3 under the Wet Pendulum Test as defined in AS4586. These ratings indicate a reduced risk of slip with this product.
- Sound Rating The Now Collection reduces impact sound by 12 decibels when adhered directly to a concrete slab. The Now Collection reduces airborne sound by 5% when adhered to a concrete slab. This is comparable to the effect that direct stick carpet would achieve.
- Installation Please refer to Bolon Installation Guidelines or contact the Customer Service Team at The Andrews Group
+61 (03) 9827 1311 | bolon@theandrewsgroup.com.au
- Maintenance Please refer to Bolon Maintenance Guidelines or contact the Customer Service Team at The Andrews Group
+61 (03) 9827 1311 | bolon@theandrewsgroup.com.au