

# BOLON FLOORING

# BOLON BY PATRICIA URQUIOLA

## TECHNICAL SPECIFICATION

Woven vinyl flooring, product standard EN 1307.

INCLUDED IN EN 1307		ROLLS	
	Use classification	ISO 10874	33 Heavy Commercial
	Weight	ISO 8543	3,1 kg/m <sup>2</sup>
	Thickness	ISO 1765	2,4 mm
	Roll dimension	EN 426	2000 mm, 25 m
	Tile dimension	EN 994	-
	Castor Chair	EN 985	Intensive use
	Body Voltage	EN 1815**	Fulfilled
	Thermal resistance	ISO 8302	Suitable for underfloor heating
	Impact sound insulation*	EN ISO 10140	9 dB
	Airborne sound absorption*	EN ISO 354 $\alpha_w$	0,05
	Airborne sound absorption*	EN ISO 354 $\alpha_s$	250 Hz 0,01 500 Hz 0,01 1000 Hz 0,05 2000 Hz 0,09
	Colour fastness to light*	EN ISO 105-B02	> 7
	Dimension stability	ISO 2551 EN 986	Fulfilled
<b>ADDITIONAL TESTS</b>			
	Anti slip property	DIN 51130	R9
	Friction	EN 13893	> 0,3
	Pendulum	EN 13036-4	88-93
	Reaction to fire	EN 13501-1	B <sub>fl</sub> -s1
	Critical radiant flux	ASTM E 648	Class 1
	Smoke density	ASTM E 662	< 450

\* Typical value

\*\* EN 1815 replaces ISO 6356

# BOLON FLOORING

# BOLON BY PATRICIA URQUIOLA

## CERTIFICATES AND SUSTAINABILITY

For complete information and market specific certificate, visit [bolon.com](http://bolon.com) or contact customer service.

SUSTAINABILITY		ROLLS
Recycled content	ISO 14021	18% Pre-consumer material
Carbon footprint CO2e/m <sup>2</sup>	EN 15804 (A1-A3)	5,74
CERTIFICATES		
CE		419005
Emissions		M1, Floorscore, VOC A+
Raw material		Best Practice PVC
LCA		EPD, GreenTag
Content/chemicals		GreenTagPHD, Follows req. of BASTA
REGISTRATED		
BASTA		Yes
BRE Global Listed		Yes
Byggarbedömningen		Yes
DGNB navigator		Yes
eBVD		Yes
ECOproduct		Yes
GBR kretsloppsmärkning		Yes
SundaHus		Yes



# BOLON

Bolon HQ: Industrivägen 12, 523 90 Ulricehamn, Sweden  
[bolon.com](http://bolon.com) | [info@bolon.com](mailto:info@bolon.com) | [@bolonofficial](https://twitter.com/bolonofficial)

June, 2021